

DONGGUAN HEADQUARTER | WUHAN MARKETING CENTER | NANJING R&D CENTER
SHENZHEN | SOUTH AFRICA | GERMANY | UNITED STATES | HUNGARY



CONTACT US

Version: V3.3

Web: www.lithiumvalley.com / www.essvalley.com

Domestic Business: Roy Gao

Tel: +86 13380788260

Email: roy@lithiumvalley.com

Oversea Business: Christin Hsu

Tel: +86 18018761760

Email: christin@lithiumvalley.com

Factory Address 1: No. 11, Yinyang Road, Zhangyang Community, Zhangmutou Town, Dongguan

Factory Address 2: No.4, Fuzhu 4th Street, Zhangyang Community, Zhangmutou Town, Dongguan

Shenzhen Office: Room 2018, Huilong Business Center, Minzhi Street, Longhua District, Shenzhen

Wuhan Office: Room 208, Wanqili yi space, Optics Valley Avenue, Jiangxia District, Wuhan

Nanjing Office: Room 310, Floor 3, Park Service Center Building, No. 15, Fengji Avenue, Yuhuatai District, Nanjing



www.lithiumvalley.com

One-stop Energy Storage System Integration Supplier

**Dongguan Lithium Valley
Energy Co.,Ltd.**

Contents

Company Profile	01/04
Certification	05/06
Residential BESS	07/20
All-in-one Stackable ESS	21/28
Commercial & Industrial ESS	29/42
Project Case	43/46
Global Market & Service	47/52

3U Rack Battery
LV-BAT-R5.12Aa

Wall-mounted Home Energy Storage
LV-BAT-W5.12Ac
LV-BAT-W10.24Ac
LV-BAT-W15.36Ac

Stackable Home Energy Storage
LV-BAT-L2.56Ba
LV-BAT-L5.12Aa
LV-BAT-H2.56Aa
LV-BAT-H5.12Aa

All-in-one Stackable ESS
LV-AST-1L10K5.12Aa
LV-AST-1L6K5.12Aa
LV-AST-3H12K5.32Aa

Small-scale Industrial & Commercial ESS
30kW/60kWh 50kW/100kWh 100kW/200kWh

Medium-sized Industrial & Commercial ESS
250kW/500kWh 500kW/1MWh 1MW/2MWh

***Making the world
a green valley!***

ABOUT Lithium Valley

Dongguan Lithium Valley Energy Co., Ltd., a subsidiary of Zongshen Power (001696.SZ), was founded in 2013. With the vision of "Making the world a green valley", Lithium Valley specializes in providing customized energy storage products and comprehensive one-stop energy storage solutions for residential and commercial applications. Our products have obtained internationally recognized certifications such as CB, CE, UL1973, UL9540A, BIS, ISO9001 & ISO14001, and ISO14064 & ISO14067.

With over 16 years of battery industry experience, our founder leads the company in its pursuit of excellence. Our facilities cover an area of 30,000 square meters, and we employ over 300 professionals in management, research and development, and production roles. We have established a presence in various locations, including our headquarters in Dongguan, marketing centers in Wuhan and Shenzhen, and an R&D center in Nanjing. Additionally, we have branches in Germany, the USA, Hungary, and South Africa.

After more than a decade of industry cultivation, Lithium Valley upholds the principles of high quality, high efficiency, and sustainable development in our production and manufacturing processes. We have established a scientific and stable supply chain system, working closely with top battery cell suppliers to ensure the quality and stability of our systems from the source. These systems are integrated with our self-developed BMS battery management system, EMS energy management system, and cloud platform. Through our self-developed MES system, our quality control team monitors the entire production process rigorously. Each product undergoes a series of stringent tests before leaving the factory, ensuring its reliability and stability.



30000m²

FACTORY AREA

\$10 M

REGISTERED CAPITAL

2GWh+

DELIVERED CAPACITY


Powered by

ZONGSHEN POWER(001696.SZ)

Service

LOCAL SERVICE& INVENTORY IN EUROPE

One-stop Energy Storage Integrated Supply Solution
Making Energy Storage Integration More Secure and Worry-free



Company Culture



Dedication
Maximise initiative and creativity in working towards your goals



Innovative
Good solutions for customers through technological innovation



Cooperation
Taking a long-term view and constantly pursuing excellence in cooperation



Win-Win
Learn from each other, complement each other's strengths and help each other

Authoritative Certification

Lithium Valley products have been certified by multiple global third-party testing organization, with certification coverage spanning over 50 countries and regions worldwide.



Quality Management



ISO 9001

ISO 14001

ISO 14067


ISO 14064

Certifications


Lithium Valley technology

UL 1973

UL 9540A




CB




CE-GPSD



CE EMC




UKCA



PICC

UN38.3



MSDS





Residential BESS


Discover the Joys of Eco-Life with Lithium Valley

Imagine a world where you have complete control over your home's energy consumption, reducing your carbon footprint and saving on utility bills. A better life is not merely a dream, but a reality that we can create for you.



Smart Charge/Discharge Control

Allow homeowners to optimize their energy usage and reduce waste by managing peak demand periods.



Advanced Battery Management System

The self-developed BMS constantly monitors the battery's temperature, voltage, and current to prevent overcharging, overheating, and other potential hazards. It also optimizes the battery's charge and discharge cycles to maximize its lifespan and efficiency.



Seamless Integration

With our products, it will be easy to seamlessly integrate with your home's existing solar panels and inverters, making installation quick and easy.



Environmentally Friendly

From reduced carbon emissions to increased energy savings, we've got you covered. It will help reduce your carbon footprint by storing energy from renewable sources like solar power and wind power.



Long-Lasting Performance

Our batteries have a long lifespan (≥ 6000 cycles) and retain their performance even after years of use.

3U RACK BATTERY

Whether installed in a cabinet, stacked, or even mounted on the wall, our 3U energy storage battery provides a flexible and versatile solution. Experience durable and long-lasting energy storage in every unique scenario.



Scalable Design



Flexible Assembly



Real-time Monitoring



Efficient Performance



Safety Features



Compatibility



Cost-Effective



Durability



Model		LV-BAT-R5.12Aa
Nominal Voltage(Vdc)		51.2
Nominal Capacity(Wh)		5120
Working Voltage Range(Vdc)		44.8~56.16
Charge Voltage(Vdc)		58.4
Nominal Charge/Discharge Current(A)		50
Max.Charge/Discharge Current(A)		100
Peak Current(A)		200@3sec
Parallel Connection		≤ 16 pcs
Cycle Life		6000 @ 80% DOD, 25℃ / 0.5C
Structure		
Dimension(mm)		550*440*130
Weight(Kg)		47.2
IP Rating		IP20
Installation		Rack mounted/Wall mounted/Cabinet mounted
Working Environment		
Charge Working Temperature(℃)		0~55
Discharge Working Temperature(℃)		-20~60
Altitude(M)		<2500
Humidity(RH)		5~95%(w/o condensing)
Communication		
Communication Port		RS485,CAN
Display		SOC status indicator, LED indicator
Certification		
		CB, IEC62619, UL1973, UL9540A, UKCA, CE-EMC, CE-GPSP, EN62619 ; UN38.3, MSDS

WALL-MOUNTED HOME ENERGY STORAGE

A sleek and space-saving solution for your energy storage needs. With its compact design and easy installation, it seamlessly blends into any environment. Whether in your home, office, or commercial space, our wall-mounted unit provides reliable and efficient energy storage, empowering you to optimize energy usage and reduce waste.


- 
Space Saving
- 
Customized Panel
- 
Efficient Performance
- 
Safe and Reliable
- 
Real-time Monitoring
- 
Durability
- 
Intelligent BMS
- 
Cost Effective




Model	LV-BAT-W5.12Ac	LV-BAT-W10.24Ac	LV-BAT-W15.36Ac
Nominal Voltage(Vdc)	51.2	51.2	51.2
Nominal Capacity(Wh)	5120	10240	15360
Working Voltage Range(Vdc)	44.8~56.16	44.8~56.16	44.8~56.16
Charge Voltage(Vdc)	58.4	58.4	58.4
Nominal Charge/Discharge Current(A)	50	100	100
Max.Charge/Discharge Current(A)	100	200	200
Peak Current(A)	200@3sec	400@3sec	600@3sec
Parallel Connection	≤ 16 pcs		
Cycle Life	6000 @ 80% DOD, 25℃ / 0.5C		
Structure			
Dimension(mm)	520*470*142	800*590*142	856*820*176
Weight(Kg)	47.2	93.5	140.7
IP Rating	IP65		
Installation	Wall mounted/Floor stand		
Working Environment			
Charge Working Temperature(℃)	0~55		
Discharge Working Temperature(℃)	-20~60		
Altitude(M)	<2500		
Humidity(RH)	5~95%(w/o condensing)		
Communication			
Communication Port	RS485,CAN		
Display	SOC status indicator, LED indicator		
Certification			
CB, IEC62619, UL1973, UKCA, CE-EMC, CE-GPSP, EN62619 ; UN38.3, MSDS			



Self-developed BMS



Working Mode



STACKABLE HOME ENERGY STORAGE

With its modular design, the Multi-functional Energy Storage System offers endless possibilities. Customize the system to meet your specific needs by easily adding or removing energy storage units. Experience the freedom and control of managing your energy consumption with this state-of-the-art system.



High Capacity



Scalable Design



Efficient Performance



Safe and Reliable



Real-time Monitoring



Durability



Intelligent BMS



Seamless Integration



Model	LV-BST-L2.56Ba	LV-BST-L5.12Aa
Nominal Voltage(Vdc)	51.2	51.2
Nominal Capacity(Wh)	2560	5120
Working Voltage Range(Vdc)	44.8~56.16	44.8~56.16
Charge Voltage(Vdc)	58.4	58.4
Nominal Charge/Discharge Current(A)	25	50
Max.Charge/Discharge Current(A)	50	100
Peak Current(A)	100@3sec	200@3sec
Parallel Connection	≤ 10 pcs	≤ 6 pcs
Cycle Life	6000 @ 80% DOD, 25℃ / 0.5C	
Structure		
Dimension(mm)	600*210*180	600*210*300
Weight(Kg)	29	50.5
IP Rating	IP65	
Installation	Stacked	
Working Environment		
Charge Working Temperature(℃)	0~55	
Discharge Working Temperature(℃)	-20~60	
Altitude(M)	<2500	
Humidity(RH)	5~95%(w/o condensing)	
Communication		
Communication Port	RS485,CAN	
Display	SOC status indicator, LED indicator	
Certification		
CB, IEC62619; CE-EMC, CE-GPSPD, UKCA; UN38.3, MSDS		

HIGH-VOLTAGE STACKABLE ENERGY STORAGE

Power up your energy storage game with compact size, lightweight design, and effortless installation of standardized modules, leveraging the advantages of high voltage. Effortlessly customize battery combinations to meet your energy storage needs.


High Capacity


Scalable Design


Efficient Performance


Safe and Reliable


Real-time Monitoring


High Voltage


Intelligent BMS


Seamless Integration




Model	LV-BST-H2.56Aa	LV-BST-H5.12Aa
Nominal Voltage(Vdc)	51.2	51.2
Nominal Capacity(Wh)	2560	5120
Working Voltage Range(Vdc)	129.6-516.6	129.6-350.4
Charge Voltage(Vdc)	56.16	56.16
Nominal Charge/Discharge Current(A)	25	50
Max.Charge/Discharge Current(A)	50	100
Peak Current(A)	100@3sec	200@3sec
Series Connection	3-10 pcs	3-6 pcs
Cycle Life	6000 @ 80% DOD, 25℃ / 0.5C	
Structure		
Power Module Dimensions(mm)/Weight(kg)	600*210*250/14	610*225*250/15
Battery Module Dimensions(mm)/Weight(kg)	600*210*160 /27	610*225*250/52
Lampstand Module Dimensions(mm)/Weight(kg)	600*210*90/5	610*225*90/5.5
Top Cap Module Dimensions(mm)/Weight(kg)	600*210*50/2.5	610*225*50/3
IP Rating	IP65	
Installation	Stacked	
Working Environment		
Charge Working Temperature(℃)	0~55	
Discharge Working Temperature(℃)	-20~60	
Altitude(M)	<2500	
Humidity(RH)	5~95%(w/o condensing)	
Communication		
Communication Port	RS485,CAN	
Display	SOC status indicator, LED indicator	
Certification		
CB, IEC62619, CE-EMC, CE-GPSPD, UKCA, UL1973, UL9540A, EN62040, IEC62040; UN38.3, MSDS		



THERMAL AEROSOL FIRE SUPPRESSION DEVICE

The energy storage system is equipped with a breakthrough aerosol fire suppression device, boasting ultra-high efficiency and reliability. Its compact size, rapid response, and eco-friendly features make it ideal for enclosed spaces like battery compartments. Invest in our ESS today for top-of-the-line fire protection technology to ensure the safety of personnel and property.



3-10 Modules Stackable → 153.6V-512V High Voltage

- Higher Conversion Efficiency
- Better Suitable for Peaking Applications
- Greater Flexibility
- Faster Charging and Discharging
- Energy Savings
- Increased Independence from the Grid
- Lower Cost, Larger System



LV-BAT-H2.56Aa

ALL-IN-ONE STACKABLE ESS(US)

An efficient, safe, and intelligent home energy storage solution, featuring a convenient modular battery design and integrated inverter, EMS, and UPS management system. Seamlessly switch between power sources, remotely control your energy needs, and customize intelligent operating plans.


High Capacity


Compact Design


All-In-One Design


Scalable Design


Sustainability


Remote Monitoring


IP65


Enhanced Resilience

INVERTER
MODULE

BATTERY
MODULE

Battery Module		LV-AST-1L10K5.12Aa	
	1 layer	2 layers	3 layers
			
Model	51.2V 200Ah	51.2V 300Ah/400Ah	51.2V 500Ah/600Ah
Energy(kWh)	10.24	15.36/20.48	25.6/30.72
Operating Voltage Range(V)	44.8～56.16		
Cell Technology	Lithium iron phosphate (LiFePO4)		
Life Cycle	6000 @ 80% DOD , 25°C / 0.5C		
Charge/Discharge Current(A)	195		
Dimension(L*W*H)(mm)	653*301.5*1368	653*301.5* 1886	653*301.5*2404
Weight(Kg)	200	260/320	380/440
AC			
Rate AC Output Power(kW)	8～10		
AC Output Voltage	120/240Vac(split phase), 230Vac(single phase)		
AC Output Frequency(Hz)	50/60		
Grid Connection	Split phase, single phase		
General Data			
Display	LCD		
Communication	CAN, RS485, WIFI		
Operating Temperature	-10°C～55°C		
IP Rating	IP65		
Cooling	Fan cooling		
Certification	UL9540A, UL9540, MSDS, UN38.3		

ALL-IN-ONE STACKABLE ESS(EU)

An efficient, safe, and intelligent home energy storage solution, featuring a convenient modular battery design and integrated inverter, EMS, and UPS management system. Seamlessly switch between power sources, remotely control your energy needs, and customize intelligent operating plans.



High Capacity



Compact Design



All-In-One Design



Scalable Design



Sustainability




Remote Monitoring



IP65



Enhanced Resilience



INVERTER
MODULE

BATTERY
MODULE

Battery Module		LV-AST-1L6K5.12Aa	
	1 layer	2 layers	3 layers
			
Model	51.2V 200Ah	51.2V 300Ah/400Ah	51.2V 500Ah/600Ah
Energy(kWh)	10.24	15.36/20.48	25.6/30.72
Operating Voltage Range(V)	44.8 ~56.16		
Cell Technology	Lithium iron phosphate (LiFePO4)		
Life Cycle	6000 @ 80% DOD , 25°C / 0.5C		
Charge/Discharge Current(A)	120		
Dimension(L*W*H)(mm)	653*320*1400	653*320* 1950	653*320*2500
Weight(Kg)	200	260/320	380/440
AC Output			
Nominal AC Output Power(kW)	6		
Grid Voltage/Range(V)	220/210-230		
Rated Grid Frequency(Hz)	50/60		
Grid Connecion	Single phase		
General Data			
Display	LCD		
Communication	CAN, RS485, WIFI, Bluetooth		
Operating Temperature	-10°C ~55°C		
IP Rating	IP65		
Cooling	Natural convection		
Certification	IEC62477, IEC62109; UN38.3, MSDS		

HIGH-VOLTAGE ALL-IN-ONE STACKABLE ESS

An efficient, safe, and intelligent home energy storage solution, featuring a convenient modular battery design and integrated inverter, EMS, and UPS management system. Seamlessly switch between power sources, remotely control your energy needs, and customize intelligent operating plans.



High Capacity



Compact Design



All-In-One Design



Scalable Design



Sustainability



Remote Monitoring



IP65



Enhanced Resilience





Battery Module		LV-AST-3H12K5.32Aa	
	2 layers	3 layers	
			
Model	410V 52Ah	614V 52Ah	
Energy(kWh)	21.30	31.95	
Operating Voltage Range(V)	358.4~449.28	576~700	
Life Cycle	6000 @ 80% DOD , 25°C / 0.5C		
Charge/Discharge Current(A)	50	50	
Dimension(L*W*H)(mm)	653*301.5*1846	653*301.5*2364	
Weight(Kg)	320	440	
AC			
Rate AC Output Power(kW)	12		
Grid Voltage/Range(V)	400 /360~440		
AC Output Frequency(Hz)	50/60		
Grid Connection	3W+N+PE		
General Data			
Display	LCD		
Communication	CAN, RS485, WIFI		
Operating Temperature	-10°C ~55°C		
IP Rating	IP65		
Cooling	Natural Convection		
Certification	IEC62477, IEC62109; UN38.3, MSDS		



How about a peaceful slumber every night, with an uninterrupted supply of abundant electricity?


1. Energy Storage: Lithium Valley residential ESS stores excess energy from solar panels or the grid, which you can use during peak hours when electricity rates are higher. By using stored energy instead of drawing from the grid, you can reduce your electricity bill.



2. Time-of-Use Optimization: Some utility companies offer time-of-use (TOU) pricing, where the cost of electricity varies depending on the time of day. With a Residential ESS, you can store energy during off-peak hours when prices are low and use it during peak hours when prices are high. This way, you can take advantage of TOU pricing and save money on your bills.

There is no need to stress over the cost — simply embrace the future of sustainable living with our innovative residential BESS.

3. Backup Power: During power outages, a Residential ESS can provide backup power to your home. This means that you can continue to use appliances and electronics even when the grid is down. By having a reliable backup power source, you can avoid the costs associated with spoiled food and lost productivity.



4. Virtual Power Plant: A VPP aggregates the power output of multiple residential ESSs and uses them as a single resource. By participating in a VPP program, you can earn money by selling the excess energy stored in your ESS back to the grid or to other customers during periods of high demand.



Comprehensive C&I ESS Solutions For All Scenarios

- Keep your business ahead of the curve with our cutting-edge C & I ESS technology. From increased efficiency to reduced costs, the benefits are endless.
- Whether it's for large-scale industrial operations or small commercial settings, Lithium Valley's energy storage solutions offer a flexible and adaptable solution to meet the diverse needs of clients.




Peak Shifting
/Multi Purpose



Frequency
Integration



Renewable Energy
Regulation



Small-scale Commercial & Industrial ESS

Ultimate reliability and servicability:

The system achieves an incredible level of reliability through its fully modular architecture, which enables multiple levels of redundancy;

Unified monitoring and data platform:

It offers unparalleled real-time data in your pocket and on your laptop, enabling you to understand site operations anytime, anywhere;

Obsessively engineered for safety:

Eliminate diesel handling, spills and devastating diesel fires. Lack of moving parts makes the system orders of magnitude safer by design;

Support & Service:

Remotely monitored by Lithium Valley for any issues. Quick and dedicated service team to support you on site.



Model	30kW/60kWh	50kW/100kWh	100kW/200kWh
Installation			
Cabinets(W*D*H)(mm)	2400*1100*2450	2400*1100*2450	2700*1100*2550
Air Conditioning Capacity	1kW	1kW*2	3kW
Battery Part			
Battery Cell(Ah)	102	100	280
PACK	1P16S	2P16S	1P16S
PACK Capacity(kWh)	5.222	10.24	14.336
PACK Size(W*D*H)(mm)	468*550*160	468*650*230	495*700*230
PCS			
Photostamper Size(W*D*H)(mm)	800*800*1900	800*800*1900	1200*800*2050
Single Battery			
Number of Packs Per Cluster	12	10	14
Single-cluster Nominal Voltage (LFP3.2V)	614.4	512	716.8
Single-cluster Voltage Range (Cell Min2.8V~Max3.65V)	537.6~700.8	448~584	627.2~817.6
BMS			
The Number of Battery Clusters	1	1	1
PACK	1P192S*1	2P160S*1	1P224S*1
Number of High Voltage BMS	2	2	2
Battery Capacity(kWh)	62.669	102.4	200.704
Number of Battery Racks (7 layers/rack)	2	2	3
PV			
PV Capacity for Connection(kWp)	60/120	60/120	120/180/240
Actual Access Capacity(kWp)	57.6	115.2	230.4
Number of PV Modules(600Wp)	96	192	384
Combiner Box Model	6 in 1 out	12 in 1 out	24 in 1 out
Number of PV Combiner Boxes	1	1	1

Medium-sized Commercial & Industrial ESS

Friendly and flexible:

- Standardized design, easy for capacity expansion, easy for maintenance;
- Independent air flow design for high reliability.

Safe and reliable:

- Support battery management system and comprehensive thermal management;
- Realize the fault classification protection algorithm.

Intelligent and efficient:

- Support real-time online monitoring of system status;
- Large capacity, long life, high discharge rate.

Abundant configuration:

- All kinds of power configuration for different projects;
- Integrated monitoring system.

Model	250kW/500kWh	500kW/1MWh	1MW/2MWh
Installation			
Container	20ft	20ft	40ft
Air Conditioning Capacity	7.5kW	7.5kW*2	15kW*2
Battery Part			
Battery Cell(Ah)	280	280	280
PACK	1P16S	1P16S	1P16S
PACK Capacity(kWh)	14.336	14.336	14.336
PACK Size(W*D*H)(mm)	495*700*230	495*700*230	495*700*230
PCS			
Photostamper Size (W*D*H)(mm)	600*720*2050 +1200*800*2050	(600*720*2050)*2 +1600*1050*2050	(600*720*2050)*3 +1600*1050*2050
Single Battery			
Number of Packs Per Cluster	12	14	14
Single-cluster Nominal Voltage (LFP3.2V)	614.4	716.8	716.8
Single-cluster Voltage Range (2.8V~3.65V)	537.6~700.8	627.2~817.6	627.2~817.6
High Voltage BMS			
Number of Battery Clusters	3	5	10
PACK	1P192S*3	1P224S*5	1P224S*5*2
Number of High Voltage BMS	3	5	10
Battery Capacity(kWh)	516.10	1003.52	2007.04
Number of Battery Racks (7 layers/rack)	6	11	22
PV			
PV Capacity for Connection(kWp)	300/360	600/660/720	1200/1320/1440
Actual Access Capacity(kWp)	345.6	691.2	1238.4
Number of PV Modules(600Wp)	576	1152	2304
Number of Assembly Components/Branches of the Bus Box	16	16	16
Combiner Box Model	18 in 1 out	24 in 1 out	24 in 1 out
Number of PV Combiner Boxes	2	3	6

Dedicated Commercial & Industrial ESS



Integrated LFP battery and intelligent fire control temperature regulation



Convenient transportation with 40-foot container integration




High reliability of the heat dissipation design system



Low loss and high safety with temperature control design



Three-level battery data management with cell data monitoring



Standard communication interface for easy system management and scheduling



Strong environmental adaptability with IP65 protection level



Ability to withstand high and low voltage variations




Container Energy Storage System

- ① High Performance and Fast Response Cooling system
- ② Safety Escape Indicator
- ③ High Safety and Long Life Battery and Protection System
- ④ High-performance Fire Extinguisher
- ⑤ Stable and Efficient Power Converter System
- ⑥ Highly Sensitive and Fast Response Fire Control system
- ⑦ 24/7 Monitoring
- ⑧ Low-energy Ventilator

Overview of Energy Storage System Applications

Grid-side/Generation-side/User-side

Grid-side: Energy storage systems balance the load on the power grid, improving its stability and reliability. They store energy during low demand periods to meet high demand during peak periods. By cutting peaks and filling valleys, they can alleviate the contradiction between supply and demand, reduce operating costs, monitor load fluctuations, and quickly respond to grid dispatches to improve frequency stability.



Generation-side: Energy storage systems improve the efficiency of renewable energy utilization and resolve issues of electricity fluctuation and instability. These systems store excess energy and release it when needed to ensure a steady supply of energy. They also improve the stability of new energy output and transient power impacts on the grid, thereby enhancing the quality of electric power.




User-side: Energy storage systems improve energy utilization efficiency and save energy consumption. For instance, solar power panels store energy during the day for use at night or during cloudy and rainy days to reduce costs. They also smooth out power delivery, increase capacity utilization, reduce transformer requirements and basic electricity fees, and generate economic benefits based on differences in peak and off-peak electricity prices.




Off-grid/Microgrid Applications

Off-grid: Off-grid system is an independent energy system that does not rely on traditional power grids. Energy storage systems typically work with renewable energy devices (such as solar panels and wind turbines) to provide safe, clean, and reliable electricity to remote or geographically challenging areas while effectively reducing power supply costs.



Microgrid Applications: Microgrid system is a distributed energy system connected to the power grid and operates in collaboration with it in a small area. It can improve autonomous power supply capability, reduce dependence on the grid, and balance loads through energy storage systems. As one of the core equipment of microgrid systems, energy storage systems ensure a smooth and reliable energy supply. Additionally, they optimize scheduling and improve the safety and stability of the grid through intelligent control.



Distributed ESS in Station Area



Features:

- ①Dynamic capacity increase of transformer in station area;
- ②The peak valley arbitrage; ③Emergency power supply guarantee;
- ④Three-phase unbalance treatment; ⑤Reactive power compensation.

Project	Diesel Generator	Flywheel Energy Storage System	Intelligent Flexible Power Supply Protection Source
function	power supply guarantee	power supply guarantee	fully functional, wide application
feature	serious environmental and noise pollution	efficient clean energy	efficient clean emnergy
on/off the grid switch	5~30s switch	10ms switch	parallel scheme: 20ms switching series UPS scheme: 0ms switch
operational and maintenance cost	high	medium	low
service life	10~20 years	5~10 years	10~20 years
power advantage	/	/	zero sensing, zero emission, low power consumption

Energy Storage System – Cloud Platform



Real-time monitoring and second-level response

High-speed data communication, second-level refresh and real-time monitoring of battery data, and visual graphics to display the operating status.

One-click inspection, intelligent operation and maintenance

The platform supports one-click inspection, real-time analysis and diagnosis, smart push of online operation and maintenance strategies and offline maintenance work orders, effectively improving the efficiency of operation and maintenance.



Data aggregation centralized display

All functions are presented as menus, which can be quickly returned or switched on any interface. The operation is simple and convenient, greatly reducing the workload of operation and maintenance.

Integrated design flexible expansion

Following the custom-designed structure, it is highly integrated and advanced, safe, efficient, and highly reliable. It has good structural scalability and is easy to expand and develop.

Virtual Power Plant

In the field of energy storage, VPP can effectively integrate and optimize various distributed energy storage systems, improving the stability and flexibility of the power grid:



Demand-side management: VPP can smooth power demand fluctuations by controlling the energy storage devices connected to the system, reducing the peak load of the power grid and thus reducing pressure on the grid.

Frequency regulation and voltage support: VPP can use energy storage systems to quickly respond to power grid frequency and voltage fluctuations, helping to maintain stable operation of the power grid.

Energy trading and market participation: VPP can integrate distributed energy storage systems into the energy market, participate in power trading, and create revenue for system owners.

Integration of renewable energy: VPP can balance the intermittency and instability of renewable energy through energy storage systems, improving the penetration rate of renewable energy in the power grid.

Emergency backup and power supply guarantee: In the event of a power grid failure or emergency, VPP can use energy storage systems to provide emergency backup power for critical loads, ensuring the reliability of power supply.



Project Case




Loiret, France Residential Photovoltaic System

15kW/30kWh+10kwp PV

2022.05

On-Grid | Self-Sufficient

Outdoor Installation



Johannesburg, SA Residential PV System

5kW/5kWh+5kwp PV

2023.03

On-Grid | Self-Sufficient

Indoor Installation



Texas, US Residential PV System

15kW/30kWh+10kwp PV

2021.07

On-Grid | Self-Sufficient

Outdoor Installation


Buenos Aires, Argentina Residential Backup Power System

10kW/20kWh+10kwp PV

2020.07

Off-Grid | Backup Power

Indoor Installation



Manila, Philippines Residential PV System

15kW/30kWh+10kwp PV 2022.10

On-Grid | Self-Sufficient Outdoor Installation

Project Case



Brandenburg, Germany Outdoor Integrated ESS

25kW/50kWh
2022.06
On-Grid | Self-Sufficient
Outdoor Cabinet



Hunan, China Microgrids

250kW/520kWh+150kwp PV 2021.05
Self-Sufficient | Backup Power Outdoor Container


Liverpool, United Kingdom ESS

500kW/1MWh
2020.10
Peak Shaving&Valley Filling |
Backup Power
Outdoor Container



Johannesburg, South Africa ESS


600kW/1224kWh
2021.05
Self-Sufficient | Backup Power
Outdoor Container



Burriam, Thailand Outdoor Integrated ESS

50kW/100kWh
2021.03
On-Grid | Backup Power
Outdoor Cabinet

Global Market





Advanced Technology

- A-Grade LFP Cell
- Self-Developed Smart BMS
- Real-Time Remote Monitoring Multi-Mode Operation
- Adaptive Energy Management System
- Enhanced Comprehensive Safety System






Stringent Quality Assurance Process

- Ongoing training for our workers
- High-quality materials and components
- Rigorous tests including battery performance testing, safety testing, and environmental adaptability testing



High-Caliber R&D Team

With 50+ R&D technicians, the main R&D staff have more than 10 years of experience in the field of lithium batteries.



Global Supply and Sales System

Our company has a global supply and sales system that allows us to serve customers all over the world. Currently, we are in the process of setting up more overseas branches and warehouses to better serve our customers worldwide.

Global Service System

Trust us to maximize the potential of your energy storage system with professionalism, expertise, and a commitment to excellence. From consultation to upgrades, we've got you covered



Pre-sales service

Free technical consultations:

- 1. Initial product overview
- 2. Technical specifications review
- 3. Customized design consultation
- 4. Site assessment

Diverse solutions:

Photovoltaic application solutions, including residential and commercial energy storage projects; Design comprehensive solutions; Determine technical solutions; Sign technical agreements.

In-sales service

On-site tracking services throughout the entire process:

Quotation and Contracting: we provide our customers with a detailed quotation outlining the cost of the proposed solution, including all components, delivery, installation, and post-sale services. Once the customer accepts the quotation, we provide a comprehensive contract that outlines all terms and conditions.

Delivery and Installation:

We take care of the entire delivery and installation process, ensuring that the batteries are installed safely and correctly. In some countries, our team of experienced professionals installs the batteries, performs necessary tests, and trains the customer on how to operate and maintain the battery system.

We support on-site inspections and result verification by customers and provide professional suggestions for optimizing solutions.



After-sales service

After-sales consulting and training services:

Professional technical support, maintenance, and repair services for our products;

Remote monitoring services to ensure that the system is operating efficiently and to identify potential issues before they become major problems;

Comprehensive warranties (5-10 years)